MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name IdeaPaint CREATE - part A (THAT) (Black version)

Version # 01

Revision date 04-24-2012 CAS # Mixture

Product code CREATE - part A (THAT)

Product use Dry erase coating.

Manufacturer/Supplier IdeaPaint

290 Eliot Street, 2nd Floor, Ashland, MA 01721

Telephone number 617.714.1050

Emergency +1.866.519.4752 (US, Canada, Mexico)

+1-760-476-3962 (US, Canada, Mexico)

Access Code: 333641

2. Hazards Identification

Physical state Solid.

Appearance Black liquid.
Emergency overview WARNING

Irritating to eyes and skin. May cause allergic skin reaction.

OSHA regulatory status

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Eyes Irritating to eyes.
Skin Irritating to skin.

InhalationProlonged inhalation may be harmful.IngestionIrritating to mouth, throat, and stomach.

Target organs Eyes. Respiratory system. Skin.

Chronic effects Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Signs and symptoms Skin irritation. Irritation of eyes and mucous membranes.

Potential environmental effects Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the

environment.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Epoxy resin	30583-72-3	15 - 40
Wollastonite	13983-17-0	10 - 30
Carbon black	1333-86-4	0.1 - 1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses

and open eyelids wide apart. Get medical attention if irritation develops or persists.

Skin contact Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. Get

medical attention if irritation develops or persists.

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center

immediately.

Ingestion Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison

control center. Do not use mouth-to-mouth method if victim ingested the substance.

Notes to physician Treat symptomatically.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire Fighting Measures

Flammable properties The product is not flammable.

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

None known.

Protection of firefighters

Specific hazards arising from the chemical

Fire or high temperatures create: Carbon oxides. Nitrogen oxides. Metal oxides.

Protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific methodsMove container from fire area if it can be done without risk. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Local authorities should be advised if significant spillages

cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this

MSDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or

onto the ground.

Methods for cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Never return spills in original containers for re-use. This material and its container must be

disposed of as hazardous waste.

Other information Clean up in accordance with all applicable regulations. Use a non-combustible material like

vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. Handling and Storage

HandlingUse Personal Protective Equipment recommended in section 8 of the MSDS. Eating, drinking,

and smoking should be prohibited in areas where this material is handled, stored, and processed. Persons with epoxy allergy should not work with this product. Avoid inhalation of vapors and contact with skin, eyes and clothing. Avoid release to the environment. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not reuse this container. "Empty" containers retain product residue (liquid or vapor) and

can be dangerous.

Storage Store in accordance with local, regional, national, and international regulations. Store in tightly

closed original container in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from incompatible materials. Keep away from food, drink and animal feeding stuffs. Do not store in unlabelled containers. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate container to avoid environmental contamination. Store at temperature

below 49°C.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Value Components **Form Type** Carbon black (1333-86-4) TWA 3 mg/m3 Inhalable fraction. US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components **Type** Value Carbon black (1333-86-4) PFI 3.5 mg/m3

Engineering controls Ensure adequate ventilation, especially in confined areas. Provide easy access to water supply

and eye wash facilities.

Personal protective equipment

Eye / face protection Chemical goggles are recommended.

Skin protection Wear protective gloves. Butyl rubber gloves are recommended. Wear suitable protective clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a properly fitted, particulate filter respirator complying with an approved

standard if a risk assessment indicates this is necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove

contaminants. Discard contaminated footwear that cannot be cleaned. Do not eat, drink or smoke when using the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Black liquid. **Appearance** Color Black.

Not assigned. Odor **Odor threshold** Not available.

Physical state Solid. **Form** Liquid.

Not available. Ηg **Melting point** Not available. Freezing point Not available.

> 100 °F (> 37.8 °C) **Boiling point**

Flash point 200 °F (93.3 °C) Closed Cup

70 (n-Butylacetate=1) **Evaporation rate**

Flammability limits in air, upper, Not available.

% by volume

Flammability limits in air, lower, Not available.

% by volume

1.6 kPa (20°C) Vapor pressure Not available. Vapor density

1.29 Specific gravity

Not available. Solubility (water) **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. < 25 g/l VOC

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions.

Conditions to avoid Keep away from heat, sparks, and flame.

Incompatible materials Water. Acids. Oxidizing material. Strong alkaline. Hazardous decomposition None expected under normal conditions of use.

products

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

11. Toxicological Information

Acute effects Irritating to eyes and skin. Material generates methanol on contact with water or moisture in eye.

skin and mucous membranes and has an irritating dehydrating effect on overexposed tissue.

Irritating to eyes and skin. May cause sensitization by skin contact. Irritating to mouth, throat, and Local effects

stomach

Sensitization May cause sensitization by skin contact.

Chronic effects Preparation contains an epoxy resin, which may cause sensitization and development of allergy.

Inhalation of carbon black dust may cause cancer, however due to the physical form of the Carcinogenicity

product, inhalation of dust is not likely.

ACGIH Carcinogens

Carbon black (CAS 1333-86-4) A3 Confirmed animal carcinogen with unknown relevance to

humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Wollastonite (CAS 13983-17-0) 3 Not classifiable as to carcinogenicity to humans.

Mutagenicity No data available.

Symptoms and target

organs

Skin irritation. Irritation of eyes and mucous membranes.

12. Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **Ecotoxicity**

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulation / **Accumulation**

Not available.

Mobility in environmental

media

Not available.

Partition coefficient (n-octanol/water)

Not available.

13. Disposal Considerations

Waste from residues / unused

products

Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all

applicable regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Basic shipping requirements:

UN3082 **UN number**

Environmentally hazardous substances, liquid, n.o.s. (Bis(1,2,2,6,6-pentam ethyl-4-piperidyl) Proper shipping name

sebacate)

Hazard class 9 Ш Packing group Labels required g

Additional information:

Special provisions 8, 146, 173, 335, IB3, T4, TP1, TP29

155 **Packaging exceptions** Packaging non bulk 203 Packaging bulk 241

IATA

Basic shipping requirements:

UN number UN3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Bis(1,2,2,6,6-pentam ethyl-4-piperidyl)

sebacate)

Hazard class

IdeaPaint CREATE - part A (THAT) (Black version) 907838 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

Ш **Packing group**

Additional information:

ERG code 9L

IMDG

Basic shipping requirements:

UN number UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(1,2,2,6,6-pentam Proper shipping name

ethyl-4-piperidyl) sebacate)

Hazard class Ш Packing group F-A, S-F EmS No.

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely No

hazardous substance (40 CRF 355, Appendix A)

Section 311/312 (40 CFR Yes

370)

Inventory etatus

State regulations

ventory status		
Country(s) or region	Inventory name On inventory (y	/es/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No
*A "Yes" indicates that all compo	nents of this product comply with the inventory requirements administered by the governing country(s)	

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Hazardous Substances (Director's): Listed substance

Carbon black (CAS 1333-86-4) Listed. Wollastonite (CAS 13983-17-0) Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon black (CAS 1333-86-4) Listed: February 21, 2003 Carcinogenic.

US - Massachusetts RTK - Substance: Listed substance

Carbon black (CAS 1333-86-4) Listed.

907838 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

US - New Jersey RTK - Substances: Listed substance

Carbon black (CAS 1333-86-4) Listed. US - Pennsylvania RTK - Hazardous Substances: Listed substance

Carbon black (CAS 1333-86-4) Listed.

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 2

> Flammability: 1 Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Issue date 04-24-2012

IdeaPaint CREATE - part A (THAT) (Black version)

CPH MSDS US 907838 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name IdeaPaint CREATE - part B (THIS) (Black version)

Version # 01

Revision date 04-24-2012 CAS # Mixture

Product code CREATE- part B(THIS)(Black Version)

Product use Dry erase coating.

Manufacturer/Supplier IdeaPaint

290 Eliot Street, 2nd Floor, Ashland, MA 01721

Telephone number 617.714.1050

Emergency +1.866.519.4752 (US, Canada, Mexico)

+1-760-476-3962 (US, Canada, Mexico)

Access Code: 333641

2. Hazards Identification

Physical state Liquid.

Appearance Transparent liquid

Emergency overview WARNING

Irritating to eyes and skin. May be harmful if swallowed.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Eyes Irritating to eyes.

Skin Irritating to skin.

Inhalation Prolonged inhalation may be harmful.

Ingestion Irritating to mouth, throat, and stomach. May be harmful if swallowed.

Target organs Eyes. Respiratory system. Skin.

Chronic effects Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Signs and symptoms Skin irritation. Irritation of eyes and mucous membranes.

Potential environmental effects Toxic to aquatic organisms. May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Components	CAS#	Percent
n-[3-(Trimethoxysilyl)propyl]butylamine	31024-56-3	35-90
n-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	15-40
Dibutyltin dilaurate	77-58-7	0.5-7.5

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses

and open eyelids wide apart. Get medical attention if irritation develops or persists.

Skin contact Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. Get

medical attention if irritation develops or persists.

IdeaPaint CREATE - part B (THIS) (Black version)
907847 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center

immediately.

Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Have victim rinse

mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use

mouth-to-mouth method if victim ingested the substance.

Notes to physician Treat symptomatically.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire Fighting Measures

Flammable properties The product is not flammable.

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

None known.

Protection of firefighters

Specific hazards arising from the chemical

Protective equipment and precautions for firefighters Fire or high temperatures create: Carbon oxides. Nitrogen oxides. Metal oxides.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific methods

Move container from fire area if it can be done without risk. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Local authorities should be advised if significant spillages

> cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this

MSDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or

onto the ground.

Methods for cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Never return spills in original containers for re-use. This material and its container must be

disposed of as hazardous waste.

Other information Clean up in accordance with all applicable regulations. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

7. Handling and Storage

Handling

Use Personal Protective Equipment recommended in section 8 of the MSDS. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Persons with epoxy allergy should not work with this product. Avoid inhalation of vapors and contact with skin, eyes and clothing. Avoid release to the environment. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not reuse this container. "Empty" containers retain product residue (liquid or vapor) and can be dangerous.

Storage

Store in accordance with local, regional, national, and international regulations. Store in tightly closed original container in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from incompatible materials. Keep away from food, drink and animal feeding stuffs. Do not store in unlabelled containers. Keep container tightly closed and in a well-ventilated place. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate container to avoid environmental contamination. Store at temperature below 49°C.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US	ACGIH	Threshold	I imit	Values

Components	Туре	Value	
Dibutyltin dilaurate (77-58-7)	STEL	0.2 mg/m3	
(11-30-1)	TWA	0.1 mg/m3	
US. OSHA Table Z-1 Limits for	r Air Contaminants (29 CFR 1910.	1000)	
Components	Type	Value	
Dibutyltin dilaurate (77-58-7)	PEL	0.1 mg/m3	

Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide easy access to water supply

and eye wash facilities.

Personal protective equipment

Eye / face protection Chemical goggles are recommended.

Skin protection Wear protective gloves. Butyl rubber gloves are recommended. Wear suitable protective clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators. Use a properly fitted, particulate filter respirator complying with an approved

standard if a risk assessment indicates this is necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. Do not eat, drink or smoke when using the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Transparent liquid **Appearance**

Color Clear.

Slight ammonia. Odor **Odor threshold** Not available. Physical state Liquid.

Liquid. **Form**

Not available. pН Melting point Not available. Freezing point Not available. **Boiling point** Not available. Not available. Flash point Not available. **Evaporation rate** Flammability limits in air, upper, Not available.

% by volume

% by volume

Flammability limits in air, lower, Not available.

Vapor pressure Not available. Vapor density Not available. Specific gravity Not available. Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature

Not available.

CPH MSDS US

907847 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

Decomposition temperature Not available. **VOC** < 99 g/l

10. Chemical Stability & Reactivity Information

Chemical stability Stable at normal conditions.

Conditions to avoid Keep away from heat, sparks, and flame.

Incompatible materials Peroxides. Oxidizing agents. Acids. Alcohols. Reducing agents. Bases.

Hazardous decomposition

products

None expected under normal conditions of use.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

11. Toxicological Information

Acute effects Irritating to eyes and skin. Material generates methanol on contact with water or moisture in eye,

skin and mucous membranes and has an irritating dehydrating effect on overexposed tissue.

Local effects Harmful if swallowed. Components of the product may be absorbed into the body through the

skin. Contact may irritate or burn eyes. May cause sensitization by skin contact.

US ACGIH Threshold Limit Values: Skin designation

Dibutyltin dilaurate (CAS 77-58-7)

Can be absorbed through the skin.

Sensitization May cause sensitization by skin contact.

Chronic effects Prolonged exposure may cause chronic effects.

Carcinogenicity No data available.

ACGIH Carcinogens

Dibutyltin dilaurate (CAS 77-58-7)

A4 Not classifiable as a human carcinogen.

Mutagenicity No data available.

Symptoms and target

organs

Skin irritation. Irritation of eyes and mucous membranes.

12. Ecological Information

EcotoxicityToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulation /

llation / Not available.

Accumulation

Mobility in environmental Not available.

media

Partition coefficient Not available.

(n-octanol/water)

13. Disposal Considerations

Waste from residues / unused

products

Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all

applicable regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Basic shipping requirements:

UN number UN3082

Proper shipping name Environmentally hazardous substances, liquid, n.o.s. (Dibutyltin dilaurate)

Hazard class 9
Packing group III
Environmental hazards

Marine pollutant Yes
Labels required 9

Additional information:

Special provisions 8, 146, 335, IB3, T4, TP1, TP29

907847 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

Packaging exceptions 155

Packaging non bulk 203 Packaging bulk 241

IATA

Basic shipping requirements:

UN number UN3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Dibutyltin dilaurate)

Hazard class 9
Packing group III
Environmental hazards

Livii oiiiioittai iiazai ao

Marine pollutant Yes

Additional information:

ERG code 9L

IMDG

Basic shipping requirements:

UN number UN3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dibutyltin dilaurate)

Hazard class 9
Packing group III

Environmental hazards

Marine pollutant Yes EmS No. F-A, S-F

15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance (40

CRF 355, Appendix A)

Section 311/312 (40 CFR Yes

370)

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No

Country(s) or region Inventory name On inventory (yes/no)*

Listed.

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Dibutyltin dilaurate (CAS 77-58-7)

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2

Flammability: 0

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 0

Instability: 0

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Issue date 04-24-2012

907847 Version #: 01 Revision date: 04-24-2012 Print date: 04-24-2012

Yes