

FIXATION

Accents / Brights / Neutrals / Shapes



Construction	Tufted, Level Loop Pile
Face Fibre	Type 6 Nylon
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	420 g/m ²
Gauge	40 / 10 cm
Rows	56 / 10 cm
Tuft Density	224,000 /m ²
Finished Pile Height	3.0 mm
Standard Backing	Comfort Lite 90% Recycled content Polyurethane Available with TractionBack® on request
Nominal Total Thickness	8.8 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3700 g/m ²
Tiles per Box	22 (5.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB
Sound Absorption (ISO354)	0.3 Class D
Alpha s values	125Hz 0.02, 250Hz 0.04, 500Hz 0.51, 1000Hz 0.23, 2000Hz 0.30, 4000Hz 0.38

ENVIRONMENTAL

90% Recycled content cushion backing
 11% Recycled content by total product weight
 Manufactured in ISO14001 certified location using electricity from renewable sources
 GuT & CRI Green Label Plus certified for indoor air quality
 EPD verified - BRE certified

WARRANTIES

12 year wear warranty
 Lifetime Antistatic guarantee
 Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Zig Zag Shapes Monolithic	Brights/Neutrals/Accents Tilt/Trio Shapes Brick
----------------------------------	---

CE MARKING

--	--	--	--	--	--	--	--	--	--