

LIGHT TRAILS

Dusk / Night / Night Life



Construction	Tufted, Textured Loop Pile
Face Fibre	ECONYL® Solution-Dyed Type 6 Nylon made with 100% regenerated nylon
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	700 g/m ²
Gauge	47.2 / 10 cm
Rows	39.3 / 10 cm
Tuft Density	190,000 /m ²
Finished Pile Height	3-4 mm avg.
Standard Backing	Comfort Plus® 90% Recycled Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	10.8 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4400 g/m ²
Tiles per Box	18 (4.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB
Sound Absorption (ISO354)	0.3 Class D
Alpha s values	125Hz 0.01, 250Hz 0.09, 500Hz 0.39, 1000Hz 0.22, 2000Hz 0.32, 4000Hz 0.42

ENVIRONMENTAL

100% regenerated content yarn

Up to 32% pre-consumer recycled content and up to 10% post consumer content on total product weight

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

WARRANTIES

15 year wear warranty


Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

			ECONYL® Made with 100% Regenerated Nylon						

INSTALLATION



CE MARKING

