

OUT OF THE SHADOWS 2.0



Scattergraph / Shadowbox / Shardlines

| | |
|--------------------------------|--|
| Construction | Tufted, Textured Loop Pile |
| Face Fibre | 100% Nylon 6 including 40% ECONYL® made with 100% regenerated fibre |
| Soil Release | StainSmart® for soil release, liquid repellence |
| Finished Face Weight | 655 g/m ² |
| Gauge | 32 / 10 cm |
| Rows | 46,5 / 10 cm |
| Tuft Density | 148,000 /m ² |
| Finished Pile Height | 3.0 mm |
| Standard Backing | Comfort Plus® 90% Recycled Polyurethane cushion Available with TractionBack® on request |
| Nominal Total Thickness | 10.3 mm |
| Tile Size | 50 cm x 50 cm |
| Nominal Total Weight | 4300 g/m ² |
| Tiles per Box | 19 (4.75m ²) |

PERFORMANCE

| | |
|---|---|
| Flammability (Euroclassification EN13501:1-2002) | Class Cfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 33 dB |
| Sound Absorption (ISO354) | 0.3 Class D |
| Alpha s values | 125Hz 0.03, 250Hz 0.09, 500Hz 0.42, 1000Hz 0.26, 2000Hz 0.32, 4000Hz 0.41 |

ENVIRONMENTAL

19.5% recycled content by total product weight (3% post consumer)

40% recycled content yarn

90% recycled content cushion backing

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

BRE certified

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

| | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | |
| | | | | | | | | | | |

INSTALLATION

| | |
|---------------------------|-----------|
| Scattergraph / Shardlines | Shadowbox |
| | |
| Monolithic | Brick |

CE MARKING

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|