

# ARTISTIC LIBERTIES



Outspoken Tradition / Outspoken Tradition Inset / Historic Clashes / Historic Clashes Inset / Without Reserve

<b>Construction</b>	Tufted, Structured Loop Pile
<b>Face Fibre</b>	ECONYL® Type 6 nylon made with 100% regenerated nylon
<b>Soil Release</b>	StainSmart® for soil release, liquid repellence
<b>Finished Face Weight</b>	490 g/m <sup>2</sup>
<b>Gauge</b>	47.2 / 10 cm
<b>Rows</b>	44 / 10 cm
<b>Tuft Density</b>	224,000 /m <sup>2</sup>
<b>Finished Pile Height</b>	2.5 mm
<b>Standard Backing</b>	Comfort Lite 90% Recycled content Polyurethane cushion Available with TractionBack® on request
<b>Nominal Total Thickness</b>	8.3 mm
<b>Tile Size</b>	50 cm x 50 cm
<b>Nominal Total Weight</b>	3800 g/m <sup>2</sup>
<b>Tiles per Box</b>	22 (5.5m <sup>2</sup> )

## PERFORMANCE

<b>Flammability (Euroclassification EN13501:1-2002)</b>	Class Bfl - s1
<b>Flammability (Radiant Panel ASTM-E-648)</b>	Class 1
<b>Flammability (Hot Metal Nut BS4790)</b>	Low Radius of Char
<b>Use Classification (EN 1307)</b>	Class 33 Heavy Commercial Use
<b>Static Electricity (ISO 6356)</b>	Pass ≤ 2.0 KV Permanent Conductive Fibre
<b>Impact Sound (ISO 10140-3)</b>	31 dB
<b>Sound Absorption (ISO354)</b>	0.25 Class E
<b>Alpha s values</b>	125Hz 0.01, 250Hz 0.07, 500Hz 0.59, 1000Hz 0.18, 2000Hz 0.26, 4000Hz 0.36

## ENVIRONMENTAL

100% regenerated content yarn

90% recycled Polyurethane cushion backing  
26% recycled content including up to 9% post consumer content

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

## WARRANTIES

12 year wear warranty


Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS

			<b>ECONYL®</b> Made with 100% Regenerated Nylon						

## INSTALLATION



## CE MARKING

