

CLERKENWELL



Circle Top View / Three Corners / Time Piece / Triangular Path / Ely Place / Angled Walk / Travelling Line

Construction	Tufted, Structured Loop Pile
Face Fibre	ECONYL® Type 6 nylon made with 100% regenerated nylon
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	490 g/m ²
Gauge	47.2 / 10 cm
Rows	44 / 10 cm
Tuft Density	224,000 /m ²
Finished Pile Height	2.5 mm
Standard Backing	Comfort Lite 90% Recycled content Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	8.3 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3800 g/m ²
Tiles per Box	22 (5.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB
Sound Absorption (ISO354)	0.25 Class E
Alpha s values	125Hz 0.01, 250Hz 0.07, 500Hz 0.59, 1000Hz 0.18, 2000Hz 0.26, 4000Hz 0.36

ENVIRONMENTAL

100% regenerated content yarn

90% recycled Polyurethane cushion backing
26% recycled content including up to 9% post consumer content

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION



CE MARKING

