

# FACET

Facet / Facet Accents / Facet Transitions



<b>Construction</b>	Tufted, Level Loop Pile
<b>Face Fibre</b>	Type 6 Nylon
<b>Soil Release</b>	StainSmart® for soil release, liquid repellence
<b>Finished Face Weight</b>	420 g/m <sup>2</sup>
<b>Gauge</b>	40 / 10 cm
<b>Rows</b>	56 / 10 cm
<b>Tuft Density</b>	224,000 /m <sup>2</sup>
<b>Finished Pile Height</b>	3.0 mm
<b>Standard Backing</b>	Comfort Lite 90% Recycled content Polyurethane Available with TractionBack® on request
<b>Nominal Total Thickness</b>	8.8 mm
<b>Tile Size</b>	50 cm x 50 cm
<b>Nominal Total Weight</b>	3700 g/m <sup>2</sup>
<b>Tiles per Box</b>	22 (5.5m <sup>2</sup> )

## PERFORMANCE

<b>Flammability (Euroclassification EN13501:1-2002)</b>	Class Bfl - s1
<b>Flammability (Radiant Panel ASTM-E-648)</b>	Class 1
<b>Flammability (Hot Metal Nut BS4790)</b>	Low Radius of Char
<b>Use Classification (EN 1307)</b>	Class 33 Heavy Commercial Use
<b>Static Electricity (ISO 6356)</b>	Pass ≤ 2.0 KV Permanent Conductive Fibre
<b>Impact Sound (ISO 10140-3)</b>	30 dB
<b>Sound Absorption (ISO354)</b>	0.3 Class D
<b>Alpha s values</b>	125Hz 0.02, 250Hz 0.04, 500Hz 0.51, 1000Hz 0.23, 2000Hz 0.30, 4000Hz 0.38

## ENVIRONMENTAL


- 90% Recycled content cushion backing
- 13% Recycled content by total product weight
- Manufactured in ISO14001 certified location using electricity from renewable sources
- GuT & CRI Green Label Plus certified for indoor air quality
- EPD verified - BRE certified

## WARRANTIES

- 12 year wear warranty
- Lifetime Antistatic guarantee
- Latent Defects guarantee

## CERTIFICATIONS


## INSTALLATION



## CE MARKING

--	--	--	--	--	--