

COMFORTABLE CONCRETE 2.0



Laid Bare / Urban Drama / Urban Poetry

Construction	Tufted, Level Loop Pile
Face Fibre	Nylon 6
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	600 g/m ²
Gauge	39.4 / 10 cm
Rows	39.4 / 10 cm
Tuft Density	155,000 /m ²
Finished Pile Height	3.3 mm
Standard Backing	Comfort Plus® 90% Recycled Open Cell Polyurethane Available with TractionBack® on request
Nominal Total Thickness	10.0 mm
Nominal Total Weight	4100 g/m ²
Plank Size	50 cm x 100 cm
Planks per Box	6 (3m ²)
Tile Size	50 cm x 50 cm
Tiles per Box	20 (5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB
Sound Absorption (ISO354)	0.3 Class D
Alpha s values	125Hz 0.01, 250Hz 0.07, 500Hz 0.37, 1000Hz 0.23, 2000Hz 0.30, 4000Hz 0.38

ENVIRONMENTAL

- 59% recycled content by total product weight
- Manufactured in ISO14001 certified location using electricity from renewable sources
- GuT & CRI Green Label Plus certified for indoor air quality
- BRE certified

WARRANTIES

- 15 year wear warranty
- Lifetime Antistatic guarantee
- Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Monolithic	Monolithic	Brick	Herringbone

CE MARKING

0328-CFD-100401 EN 14041:2004				