

	Standard	Result	Product	Size (mm)
		See separate table	RCT6301	307 x 600
		2G	RCT6302	307 x 600
	ISO 24346	6,5 mm	RCT6303	307 x 600
	ISO 24340	0,55 mm	RCT6304	307 x 600
		K-Guard+ PU coating	RCP6501	1220 x 179
	Commercial	12 years *	RCP6503	1220 x 179
	Residential	30 years*	RCP6504	1220 x 179
		Micro	RCP6506	1220 x 179
	ISO 23997	7480 g/m ²	RCP6507	1220 x 179
	EN 16511	Multilayer modular floorcovering panels	RCP6508	1220 x 179
			RCP6509	1220 x 179
	ISO 10874 Commercial	33:-commercial heavy	RCP6510	1220 x 179
	ISO 10874 Domestic	23:-Domestic heavy		
	EN13501-1	B _{fl} -s1		
	EN 438-2	pass (grade 5)		
	EN ISO 105-B02	pass ≥6		
	EN13329 Annex E	pass 4000 cycles		
	EN424	pass (no visible damage)		
	EN ISO 23999	pass ≤0,25%		
	ISO 24336	pass (0,2 %)		
	EN ISO 10140-1:2016 and	ΔL _w = 19 dB		
	EN ISO 10140-3:2010+A1:2015	ΔL _{LIN} = 11 dB		
	ISO 24343-1	Pass ≤ 0,1 mm		
	EN13329 Annex F	pass ≥1800 mm		
	ISO 4918/ EN 425	pass 25 000 cycles		
	ISO 8302	0,052 m ² K/W		
		suitable for underfloor heating max 27 °C		
	EN 13893	DS		
	DIN 51130	R10		
	French VOC regulation (ISO 16000)	A+		
		None required; please install according to our installation instructions.		
		Suitable		
		Yes		

*Produced under Licence from Valinge Innovations

**subject to terms see website

***Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132
 Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14
 Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204
 Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386
 e: info@designflooring.com
www.designflooring.com

Manufactured to ISO9001



EN 14041:2004 (DOP 2017/Pcore/EN/01)
Notified body 0321
Floor Coverings (internal)
ISO 10874 Class 23/33
Manufactured to EN 16511

17

